

Enable and Disable DNS for server hostname while adding in servers and for control panel access

12 admin December 15, 2023 [Features & Functionalities](#) 4906

Server hostnames does not have DNS(Server hostname has no FQDN)? How to add the server with ip alone? How to disable DNS globally? How to enable dns resolution for control panel logins?

To set the default DNS setting globally, go to

Settings->General->Miscellaneous->Use *DNS*

Ezeelogin

Welcome, Administrator Logout

Servers

Web Portals

Users

Access Control

Settings

General

Branding

Control Panels

Data Centers

API

LDAP

SAML

FIDO2

RADIUS

SIEM

Server Fields

Cluster

Command Guard

Account

General Settings

AuthenticationTwo Factor AuthenticationSecurityDefaultsMiscellaneous

Gateway SSH Port

22

SSH Timeout

10

RDP Proxy Port

22555

Web SSH Port

52222

Web Proxy Port

52666

Web Proxy Session Timeout

300

Web Proxy Request Timeout

120

Web Proxy Web Sockets

☒

Web Proxy Forwarded Header

☒

Log Retain Duration (months)

0

Log Space Threshold (MB)

0

mExec Concurrency

100

NodeJS Command

/usr/bin/nodejs

Hide Inbuilt Backgrounds

☐

Login theme

Dark

Use DNS

☒

Internal commands

License Timeout

DNS resolution can be disabled and a server can be added in using IP address alone. To do this, go to **Servers -> Add Server -> Advanced -> Use DNS -> NO**

Ezeelogin

Welcome, Administrator Logout

Servers

Server Groups

Super Groups

Sub SSH Users

Sub SSH User Maps

mExec lists

Import

Global Key

Key Management

Web Portals

Users

Access Control

Settings

Cluster

Command Guard

Account

Help

License

Control Panel Host

Switch User Password

First Prompt

Privilege Escalation

-- None --

Tunnel Host

Remote Console User

On Host

-- None --

Rack ID

Comments

Switch User

Password Prompt

ssword:

Root Prompt

Remote Console Host

Remote Console Password

Host Node

Machine ID

Use DNS

No

CP Use DNS

Yes

Ignore Sub SSH User

If Use DNS is **yes**, Ezeelogin will try to resolve the server hostnames using DNS instead of taking the IP provided in Ezeelogin for SSH login to the server. This can be helpful when server IPs are changing often and the DNS is kept updated (In this case, the SSH login via Ezeelogin will work correctly even if the IP in Ezeelogin is incorrect). When you choose **'inherit'** the default global values are used.

Ezeelogin

Welcome, Administrator Logout

Servers

Server Groups

Super Groups

Sub SSH Users

Sub SSH User Maps

mExec lists

Import

Global Key

Key Management

Web Portals

Users

Access Control

Settings

Cluster

Command Guard

Account

Help

License

Switch User Password

First Prompt

Privilege Escalation

-- None --

Tunnel Host

Remote Console User

On Host

-- None --

Rack ID

Comments

Password Prompt

ssword:

Root Prompt

Remote Console Host

Remote Console Password

Host Node

Machine ID

Use DNS

Inherit

Inherit

No

Yes

Inherit

Ignore Sub SSH User

To set control panel DNS setting globally go to

Settings -> General -> Miscellaneous -> CP Use DNS.

Ezeelogin

Welcome, Administrator Logout

Servers

Web Portals

Users

Access Control

Settings

General

Branding

Control Panels

Data Centers

API

LDAP

SAML

FIDO2

RADIUS

SIEM

Server Fields

Cluster

Command Guard

Account

Web Proxy Port

52666

Web Proxy Request Timeout

120

Web Proxy Forwarded Header

☒

Log Space Threshold (MB)

0

NodeJS Command

/usr/bin/nodejs

Login theme

Dark

Internal commands

☒

CP Use DNS

☒

Proxy Host

Proxy Username

Web Proxy Session Timeout

300

Web Proxy Web Sockets

☒

Log Retain Duration (months)

0

mExec Concurrency

100

Hide Inbuilt Backgrounds

☐

Use DNS

☐

License Timeout

30

Proxy Port

Proxy Password

Pass User Through

To disable DNS for control panel for a server go to **Servers -> Add Server -> Advanced-> CP Use Dns-> NO**

Ezeelogin

Welcome, Administrator Logout

Servers

Server Groups

Super Groups

Sub SSH Users

Sub SSH User Maps

mExec Jobs

Import

Global Key

Key Management

Web Portals

Users

Access Control

Settings

Cluster

Command Guard

Account

Help

ssword:

First Prompt

Root Prompt

Privilege Escalation

-- None --

Remote Console Host

Remote Console Password

Tunnel Host

Remote Console User

Host Node

☐

Machine ID

On Host

-- None --

Use DNS

Inherit

Rack ID

CP Use DNS

No

Ignore Sub SSH User

☐

Comments

To enable DNS for control panel for a server go to **Servers -> Add Server -> Advanced -> CP Use Dns -> yes**

Ezeelogin

Servers

Server Groups

Super Groups

Sub SSH Users

Sub SSH User Maps

mExec-Lists

Import

Global Key

Key Management

Web Portals

Users

Access Control

Settings

Cluster

Command Guard

Account

Help

License

SSword:

First Prompt

Privilege Escalation

-- None --

Tunnel Host

Remote Console User

On Host

-- None --

Rack ID

Comments

Root Prompt

Remote Console Host

Remote Console Password

Host Node

Machine ID

Use DNS

Inherit

CP Use DNS

Yes

Ignore Sub SSH User

IPMI

Welcome, Administrator Logout

Online URL:

<https://www.ezeelogin.com/kb/article/enable-and-disable-dns-for-server-hostname-while-adding-in-servers-and-for-control-panel-access-12.html>