User identity and access management in SSH

197 admin April 4, 2025 <u>Identity & Access Management (IAM)</u>, <u>Productivity & Efficiency</u> <u>Features</u> 29754

How to login into the remote server with the same username as the ssh gateway user?

Overview: This article explains how to ensure that an SSH gateway user logs into a remote server with the same username. It covers two methods: pass the user through by ensuring the same username exists on both the gateway and remote servers, and creating a sub SSH user with the same name across all remote servers. It also includes instructions for deleting and adding subssh user on remote servers.

There might be situations where the SSH gateway users need to log in to a remote server with the same username as the SSH gateway user.

For example: How would you ensure that your SSH gateway user 'tony' would always login into the remote server as the system user 'tony' on the remote server?



Method 1. Pass User Through

Refer to the article on **Pass-through User.**

Note: Note: You would need to ensure that a user with the same name as the jump server user exists on the remote server.

Method 2. Sub SSH User

Here is how to ensure that the SSH gateway user 'tony' would SSH into the remote server and login as the system user 'tony' on the remote server corporate.eznoc.com which belongs to the server group Linux cloud instances.



Note: Make sure to use the <u>Password Management</u> as "Automatic" or " Keep given password", or else the user won't be created on the remote servers that being added after creating sub ssh user.

Note: You can also establish a subordinate SSH user using a non-privileged user allowing a gateway user to log into the remote server as a sub ssh user.

Refer to the article for more details: Create sub ssh user with non-privileged remote ssh user

Step 1: Create the SSH gateway user 'tony'.

Ezeelogin										Welcome, Administrator
t≣ Servers ►	•	User	s find	All	~		· · · · · · · · · · · · · · · · · · ·			Rows Auto -
📲 Web Portals 🛛 🕨	×		<u>Username</u> ↓	First Name	Last Name	Email	Status	Expiry	User Group	Actions
👥 Users 🔍 🔻			ezadmin	Administrator		admin@uc.com	Active		Admins	D / T 🗎
 User Groups 			tony	tony		tony@uc.com	Active		Dummy	15 🖉 🖉
										1 - 2
			1. 1. 1. A.	14. 14.2 M 1. 19. 19. 19.	and a state of the		A Start	S. S. S. C. L.	State State State	
			in press and						and a starting	
► SCP Log				and the second states			Section Research			

Step 2: Create Sub SSH user called 'tony'. This step would create system users by the name 'tony' across the servers added in GUI. If the system user 'tony' already exist on the remote server, then select <u>unmanaged</u> while adding the system user.

Ezeelogin				Welcome, Administrator Logo
t≣ Servers ▼	Sub SSH Users find	All 🗸 🞯		Rows Auto 🗸 💿
 Server Groups 	Username ↓	Groups	Туре	Actions
 Super Groups 	tony		Managed	8.
Sub SSH Users	john		Unmanaged	/ 8
 Sub SSH User Maps 	alex		Managed	1 8
 mExec lists Import 				1-3/3
 Global Key Key Management 				

Note: You can edit the password and SSH private key of the unmanaged user 'john' by clicking the add/edit option.

Note: If the sub ssh user is unmanaged, ie if the user 'tony' already exists on remote servers, then you can generate key pair for the user 'tony' and paste the private key below. The public key needs to be entered manually on the remote servers. If you are getting the error **Wrong passphrase or corrupted key** while adding private keys refer <u>article</u>.

Step 3: Edit the user 'tony' and select the **'sub ssh user**' **'tony**' as well. This will ensure that the jump server user 'tony' will always login to the remote server as the user 'tony' itself.

Ezeelogin			Welcome, Administrator Logout
:≣ Servers ►	That is		
III Wob Portale		Edit User	
		First Name	Last Name
±t Users ▼		tony	
 User Groups 		Username 🥹	Email
 Authentication Log 		tony	tony@uc.com
▶ SSH Log	1.1.00	User Group	Status
 RDP Recording 		Dummy \$	Active X Suspended
 SCP Log Web Develop 		Evoiro (1)	Command Guard
 Web Proxy Log Web Proxy Activity 			None
 Web Activity 		Never	
 Shell Activity 		Limit IPs 🞯	Allow X Disallow
 Server Activity 		×	Virtual Shell 🐵
Work Summary	1.	Allowed IPs 🥹	×
► Status			Pass User Through @
🔒 Access Control 🛛 🕨		SSH Private Key 🐷	Inherit \$
⁰ _o Settings ►			SSH Key Passphrase 🥹
🛞 Cluster			
Command Guard		ĥ	None \$
😭 Account 🛛 🕨		Sub SSH User 🕡	Authorization Password 🥹
🛇 Help 🕨 🕨	51.0	Lony +	
License			Cancel Save
	A COM		

Step 4: SSH as gateway user 'tony' and enter to the remote server 'centos.server 'and you will be logged in as the user 'tony' on the remote server centos.server. Also, you can see that the Sub SSH User listed in the ezinfo command. The user 'tony' would be logged in as system user 'tony' on all servers.

tony@centos:~\$ whoami tony tony@centos:~\$ tony@centos:~\$ tony@centos:~\$ ezinfo	
Server decarts	
Name IP _SSH port	: centos.server : 192.168.1.36 : 22
Sub SSH User	: tony
Password	: Bm6xETfJKaTkR
Actual SSH User	: root
Actual Password	: a9sSGXWNHVgZ
SSH Kev	:BEGIN ENCRYPTED PRIVATE KEY
MIGbMFcGCSqGSIb3DQEFDTB DAYIKoZIhvcNAgkFADAdBgl 5oQFfffLg3sItBPgB0AklwR J9hkHyxQ0YoG6yNAP7c=	KMCkGCSqGSIb3DQEFDDAcBAhHI1Q/0/MJwwICCAAw ghkgBZQMEAQIEEPfmh+X5eP+6nSwt515hwt8EQMEy tZ5icgIPbqctpZs9bRdDh8RT/cBPp9rlbqjpggEwa
END ENCRYPTED PRIV	
Passphrase	: R9adKJvEmhr
Group	: production server
^C tony@centos:~\$ tony@centos:~\$	

2. Delete managed or unmanaged SubSSH users?

Step 2 (A): Click on the delete icon of the user.

Ezeelogin					Welcome, Administrator Logou
t≣ Servers ■	-				
		Sub SSH Users find	All 🗸 🖉		Rows Auto V
 Server Groups 	x	<u>Username</u> ↓	Groups	Туре	Actions
 Super Groups 		tony		Managed	
Sub SSH Users		john		Unmanaged	/ 🗄
 Sub SSH User Maps 		alex		Managed	8
 mExec lists 		alon		managoa	
► Import					1 - 3 / 3
 Global Key 					
 Key Management 	22				

Step 2 (B): Unmanaged users can simply be deleted by confirming with a click on the yes button.

Ezeelogin			Welcome, Administrator Logout
:≣ Servers ▼	Delete		
 Server Groups 			
 Super Groups 	Confirm delete: John?		
Sub SSH Users	Yes No		
 Sub SSH User Maps 		and the second	State of the second
 mExec lists 	Sub SSH Users find All 🗸 Ø		Rows Auto 🗸 🕥
► Import	Username V Groups	Туре	Actions
▹ Global Key	tony	Managed	8
 Key Management 	john	Unmanaged	<u>_</u> =
📕 Web Portais 🛛 🕨	alex	Managed	8
±t. Users ►			1-3/3

Step 2 (C): If you want to delete the **managed** user from remote servers, enable 'Delete user from server.' If you want to delete the home directory of the user from remote servers, enable 'Delete home directory.

Ezeelogin				Welcome, Administrator Logo
t≣ Servers 🗸 🍐	Delete			
Server Groups Super Groups Sub SSH Users Sub SSH User Maps mExec lists Import	Delete user from server		Delete home directory	
 Global Key 	Sub SSH Users find	All 🗸 🥐		Rows Auto 🗸 🔍
 Key Management 	Username ↓	Groups	Туре	Actions
📲 Web Portals 🛛 🕨	tony		Managed	
± Users ►	john		Unmanaged	/ 🗄
Access Control	alex		Managed	1 - 3/3
⁰₀ Settings ►				

3. How to add a SubSSH user on selected remote servers?





Step 3 (B): After selecting it will prompt for confirmation. Click on Yes for the sub ssh user creation on the selected remote servers.

Ezeelogin							2 Welcome, Administrator L	ogout
t≣ Servers ▼	Cor	nfirmation						; +
Server Groups								1
Super Groups	Set	up Sub SSH Users on selected serv	ers?	(with hach chall 15 char land nacewo	vol 4006 Bit DSA Key) using the	nalow usamamas on all sarvars. Ti	he nateway years would then	0
 Sub SSH Users 	login	via ssh into the destination servers as these set servers as keys based authentication are	e system users which would be as define more secure. Press ves to continue.	ed in the Sub SSH User Maps. Also, i	t is recommended to disable pass	word based authentication mechan	tism in sshd configuration on	-j=
 Sub SSH User Maps 	Ye	s No						
 mExec lists 	1		1200					l.
► Import	Ser	vers	All v domain lookup.				Rows Auto V	
 Global Key 								'
 Key Management 		Name V	IP Address	Server Group	SSH Port	Description	Actions	T
100		+ Developing server	192.168.56.222	Devops	22		1	e
Web Portais 🕨 🕨	0	+ centos production server	192.168.56.191	Devops	22		/	0
±t Users ►	O	+ centos7	192 168 56 181	Devops	22		1	m
	1						1 - 3 / 3	
Access Control	C.		Contract of the second second	A CONTRACTOR OF	Constant of the second		and the second second second	
⁰₀ Settings ►	-		South Carton A.	·	S. N. S. S. S.	1. A.		-

Note:

To ignore Sub SSH User for a particular remote server enable **Ignore Sub SSH User** under the Advanced Section of the Server Edit (Server ->Edit-> Ignore Sub SSH User) so that sub SSH User creation will be ignored for that remote server.

Ezeelogin		Welcome, Administrator Logout
E Servers		
▶ Server Groups	Remote Console User 🥹	Remote Console Password @
► Super Groups		
▶ Sub SSH Users	On Host @	Host Node @
 Sub SSH User Maps 		
▶ mExec lists	None 🗣	
► Import	Rack ID	Machine ID @
 Global Key 		
 Key Management 	Comments	Use DNS @
🔚 Web Portals 🛛 🕨		Inherit \$
tt Users ►	3	CP Use DNS @
Access Control		Inherit +
♥ _o Settings ►		Ignore Sub SSH User 🥥
Cluster		
Command Guard	IPMI	•

Creation of Subssh user fails

If the Ezeelogin gateway server has more remote servers, it will take more time to create the subssh user in all the servers. Refer below article to increase the execution time of the script in the gateway server.

Increase script execution time in the gateway server

Note: This feature is available from version 7.15.0 only. Refer article to <u>upgrade Ezeelogin to the latest</u> version.

Related Articles:

How to use unmanaged SubSSH users in Ezeelogin?

Access different servers with different subssh users

How to add sub ssh users on remote servers and restrict commands via sudoers file

How to add a subssh user with non privileged remote ssh login user

Online URL:

https://www.ezeelogin.com/kb/article/user-identity-and-access-management-in-ssh-197.html