## Error: Could not bind to any LDAP server: 80090308: LdapErr: DSID-0C090453, comment: AcceptSecurityContext error, data 52e, v3839

396 Nesvin KN February 6, 2025 Common Errors & Troubleshooting 15672

How to resolve error "Error: Could not bind to any LDAP server: 80090308: LdapErr: DSID-0C090434, comment: AcceptSecurityContext error, data 52e, v4f7c" ?

Overview: This article helps in resolving the error "Error: Could not bind to any LDAP server: 80090308: LdapErr: DSID-0C090434, comment: AcceptSecurityContext error, data 52e, v4f7c" encountered while saving LDAP setting in Ezeelogin GUI.

Ezeelogin Welcome, Administrator Logout						
i≣ Servers ►	Î	Error: Could not bind to any LDAP server. 80090308: LdapErr: DSID-0C090434, comment: AcceptSecurityContext error, data 52e, v4f7c X LDAP Settings				
🖬 Web Portals 🕨 🕨						
±t Users ⊳						
Access Control		Name				
°₀ Settings ▼		AD				
▶ General	1.0	URI(s) 💿				
<ul> <li>General</li> <li>Branding</li> </ul>		ktap://102.168.1.53				
<ul> <li>Control Panels</li> </ul>						
Data Centers		Start TLS @		Base DN 🐵	198	
► API		×		ou=test,dc=example,dc=com	in the	
LDAP		Bind RDN 🥥		Bind Password 💿		
► SAML		cn=Admin,cn=users,dc=example,dc=com			2.3	
► FIDO2		UID Attribute 💿		Filter 💿	1	
► RADIUS		sAMAccountName				
► SIEM						
<ul> <li>Server Fields</li> </ul>		First Name Attribute 🕡		Last Name Attribute 🥥		
🛞 Cluster		givenName				
Command Guard		Email Attribute 🥹		Group Attribute 🌚		
Command Guard		mail			and the second	
🚔 Account 🛛 🕨	-	Timeout 🥯		Rank 🌚		

The error code 52e indicates invalid credentials. Check the list below as a reference regarding all LDAP error codes.

- 525 user not found
- 52e invalid credentials
- 530 not permitted to login at this time

This error has been identified as authentication failure for service account which is used to Query the Object in LDAP Server. It often occurs when we use an incorrect attribute or password. This is a common error seen while authenticating with Windows AD server as well.

**Step 1:** Check if you have changed the password of the bind user from the LDAP server.

Step 2: Verify that the following attributes are correct. Once confirmed, try setting up LDAP

again.

- Bind DN
- Bind Password
- UID Attribute
- First Name Attribute

Refer below screenshot of LDAP settings:

Ezeelogin 🔹 Welcome, Administrator Logout				
:≣ Servers	LDAP Settings			
🔚 Web Portals	Name			
±t Users ►	ldap .			
Access Control	URI(s) 🕡			
°₀ Settings	ldap://192.168.0.110			
General	Start TLS 😡	Base DN 😡		
Branding		dc=admod,dc=ezlogin,dc=com		
<ul> <li>Control Panels</li> </ul>	Bind RDN 🕑	Bind Password 💿		
Data Centers     API	cn=admin,dc=admod,dc=ezlogin,dc=com			
► LDAP	UID Attribute 🐵	Filter 😐		
► SAML	uid			
RADIUS     Server Fields	First Name Attribute 🥹	Last Name Attribute 😡		
Cluster	givenName	sn		
	Email Attribute 📦	Group Attribute 💿		
Command Guard	mail			
Account	Timeout 👻	Rank 🐨		
🛇 Help 🕨 🕨	10 Active 🚽	10		
License		Windows Active Directory 👻		
<i>∢</i> Collapse		Cancel Save		
_		A second data to the second		

## **Related Articles:**

How to solve LDAP bind error: Invalid credentials ?

LDAP search error Cannot contact LDAP server

Ldap Failed

Could not bind to any LDAP server: error:14090086:SSL routines:ssl3\_get\_server\_certificate:certificate verify failed (self signed certificate in certificate chain)

Error: LDAP search error: Operations error

ERROR: User has not set a security code ldap sasl binds : Cannot contact LDAP server

Error: LDAP extension is not installed

Cannot contact LDAP server

Could not authenticate with any LDAP server

Online URL:

https://www.ezeelogin.com/kb/article/error-could-not-bind-to-any-ldap-server-80090308-ldaperrdsid-0c090453-comment-acceptsecuritycontext-error-data-52e-v3839-396.html