Error: SSH CONN ERROR: Cannot read property bold of undefined

511 Nesvin KN January 23, 2025 Common Errors & Troubleshooting 1934

How to fix "SSH CONN ERROR: Cannot read property 'bold' of undefined" error in Ezeelogin WebSSH

Overview: This article explains how to resolve the "SSH CONN ERROR: Cannot read property 'bold' of undefined" error in Ezeelogin WebSSH by debugging the WebSSH console, verifying SSH connectivity, and updating the SSH configuration file.

Menu SSH CONN ERROR: Cannot read property 'bold' of undefined

Refer below article to configure and troubleshoot WebSSH in Ezeelogin.

https://www.ezeelogin.com/kb/article/setup-web-ssh-console-in-ezeelogin-and-ssh-via-browser-180.html

https://www.ezeelogin.com/kb/article/could-not-setup-ezeelogin-web-ssh-service-156.html

Start the WebSSH Console node application manually to determine any errors.

root@gateway ~]# DEBUG=* PORT=52222 node \$(awk '/^system_folder/ {print \$2}' /usr/local/etc/ezlogin/ez.conf)/application/external/webssh/index.js

If the debug shows the below error then refer below steps to fix the issue.

WebSSH2 Logout: user=eztest from=192.168.1.1 host=127.0.0.1 port=36000 sessionID=undefined/uZDvv6Fk6KiLwsOcAAAA allowreplay=undefined term=xterm-color socket.io:client ignoring packet write {"type":2,"data":["ssherror","SSH CONN END BY HOST: All configured authentication methods failed"],"nsp":"/"} +2ms

In the above example, the user "eztest" tries to access the WebSSH console, and the error

"SSH CONN ERROR: Cannot read property 'bold' of undefined" appears in the console.

In the debug output, it shows "All configured authentication methods failed" for the same user, "eztest".

Follow below steps to fix the above error:

Step 1. Try to manually SSH from the gateway machine as the Ezeelogin user to localhost to confirm it is working. Additionally, ensure that password authentication is enabled for Ezeelogin users.

root@gateway ~]# ssh ezlogin_user@localhost

Step 2. If the user cannot manually SSH, allow the Ezeelogin user group in the configuration file to resolve the error. Add the following line under **Match Address 127.0.0.1.**

root@gateway ~]# vim /etc/ssh/sshd_config

Match Address 127.0.0.1

PubkeyAuthentication yes

PasswordAuthentication yes

Allowgroups ezuser

Step 3. Restart SSH daemon and try to ssh from the gateway machine as the Ezeelogin user to localhost to confirm it's working fine (refer step 1). Then click on the webssh icon on the Ezeelogin software GUI to make sure it works.

Related Articles:

"Blank page" error in webssh console

Online URL:

https://www.ezeelogin.com/kb/article/error-ssh-conn-error-cannot-read-property-bold-of-undefined-511.html