

Increase script execution time in Ubuntu and CentOS

536 Nesvin KN May 15, 2024 [General](#) 5181

How to increase script execution time in Ubuntu and CentOS?

This directive **max_execution_time** specifies the maximum time in seconds that a PHP script is allowed to run before it's terminated.

Open the **php.ini** file and change the **max_execution_time** to 300 seconds (5 minutes).

Replace the PHP version from the below command.

```
root@ubuntu ~]# php -v
PHP 7.4.3 (cli) (built: Aug 17 2022 13:29:56) ( NTS )

root@ubuntu ~]# vim /etc/php/7.4/apache2/php.ini
max_execution_time = 300
memory_limit = 256M

root@ubuntu ~]# vim /etc/php/7.4/cli/php.ini
max_execution_time = 300
memory_limit = 256M
```

To change the script execution time in CentOS 7/8.

Open the **php.ini** file and change the **max_execution_time** to 300 seconds (5 minutes).

Replace the PHP version from the below command.

```
root@centos ~]# php -v
PHP 7.4.3 (cli) (built: Aug 17 2022 13:29:56) ( NTS )

root@centos ~]# vim /etc/php.ini
max_execution_time = 300
```

```
memory_limit = 256M
```

NOTE: Execute the following command to add the new maximum execution time for apache web server using single command

```
read -p "Enter new maximum execution time (e.g., 600): " time && sed -i "s/^max_execution_time =.*/max_execution_time = $time/I" /etc/php/$(php -v | head -n 1 | awk '{print $2}' | cut -d.-f1,2)/apache2/php.ini
```

Execute the following command to add the new maximum execution time for command line

```
read -p "Enter new maximum execution time (e.g., 600): " time && sed -i "s/^max_execution_time =.*/max_execution_time = $time/I" /etc/php/$(php -v | head -n 1 | awk '{print $2}' | cut -d.-f1,2)/cli/php.ini
```

NOTE: Execute the following command to add new memory limit for apache web server

```
read -p "Enter new memory limit (e.g., 2G): " memory && sed -i "s/^memory_limit =.*/memory_limit = $memory/I" /etc/php/$(php -v | head -n 1 | awk '{print $2}' | cut -d.-f1,2)/apache2/php.ini
```

Execute the following command to add the new memory limit for command line

```
read -p "Enter new memory limit (e.g., 2G): " memory && sed -i "s/^memory_limit =.*/memory_limit = $memory/I" /etc/php/$(php -v | head -n 1 | awk '{print $2}' | cut -d.-f1,2)/cli/php.ini
```

Related Articles:

[Correct php time](#)

[PHP fatal error](#)

Online URL:

<https://www.ezeelogin.com/kb/article/increase-script-execution-time-in-ubuntu-and-centos-536.html>