

## how to create a complete backup of ezeelogin installation?

70 admin June 29, 2024 [Migration & Maintenance](#) 8466

## How do I create a complete backup of my Ezeelogin installation?

**synopsis:** The article explains how to create and restore Ezeelogin backups efficiently by skipping large log directories to speed up the process and ensuring proper configuration for successful restoration.

Execute the command **/usr/local/sbin/backup\_ezlogin.php** and this would create a binary executable backup archive in **/var/ezlogin\_backup\_xx\_x.bin**.

The directory `/var/log/ezlogin` stores the user SSH sessions that are recorded. This dir could run into a huge size ( 1GB >) which would cause the backup script to take longer to complete ( The log dir has to be tarred and then gzip'ed compressed which is time-consuming and resource intensive). In such, cases it's advisable to skip the log directory while running the backup script as follows.

```
root@Gateway:~# /usr/local/sbin/backup_ezlogin.php -nologs
```

```
root@Gateway:~# /usr/local/sbin/backup_ezlogin.php
```

\_\_\_\_  
 \_\_\_\_| | \_\_\_\_ \_(-)\_ \_\_\_\_  
 / \_ \_ / \_ / \_ | / \_ / \_ | | ' \_  
 | \_// / \_/ \_/ | (-) | (-| | | | | |  
 \_\_\_\_/\_\_\_\_|\_\_\_\_|\_\_\_\_/ \_\_, |\_\_\_\_|\_\_\_\_|\_\_\_\_|  
 |\_\_\_\_/

```
#####  
# Ezeelogin Backup #  
#####
```

```
Checking environment...
done
```

Based on your command line arguments, you may be prompted to enter the missing settings. The default value will be given in bold. Simply pressing enter key will choose the default value.

```
Creating directories... done
```

Copying files... done

```
Backup database... done
```

Backup logs... done

```
Creating executable archive... done
```

```
#####
Ezeelogin backup created: /var/ezlogin_backup_v7.37.10_b381_p8.2.20_S
at_Jun_20_2024_09_02_32_UTC.bin
(Log: /var/log/ezlogin_backup.log)
#####
```

For free assistance, please contact [support@ezeelogin.com](mailto:support@ezeelogin.com)

Thank you for choosing Ezeelogin.  
www.ezeelogin.com

- You may store this backup archive generated in /var/ezlogin\_backup.x.x remotely, in case you need to restore it when your primary node is unrecoverable.
- When your **primary node goes down**, all you need is to **migrate the license to the new IP from the portal** and **execute the backup archive on the server** and you are ready to go..

**To restore ezeelogin** , simply execute the archive created.

```
root@Gateway:~# /var/ezlogin_backup_v7.37.10_b381_p8.2.20_Sat_Jun_20_2024_09_02_32.UTC.bin
```

Creating directory ezlogin\_backup\_v7.8.0\_b381 Sat Jun 20 2024 09 10 32 UTC

Verifying archive integrity... All good.

```
Uncompressing Ezeelogin 7.8.0 backup (Thu_Oct_04_2018_09_10_32_UTC).....
```

/ \_ \_ / \_ / \_ W \_ / \_ ' \_

| \_ \_// / \_ / \_ / | ( \_ ) | ( \_ | | | |

\_ \_ / \_ \_ \_ | \_ | \_ \_ / \_ , | \_ | \_

| \_ \_ /

#####

# Ezeelogin Restore #

#####

done (1797)

Required PHP extensions...

mysqli -> Success

openssl -> Success

posix -> Success

pcre -> Success

json -> Success

curl -> Success

mcrypt -> Success

Required PHP functions...

exec -> Success

proc\_open -> Success

proc\_close -> Success

fopen -> Success

fsockopen -> Success

file -> Success

file\_get\_contents -> Success

escapeshellarg -> Success

preg\_match -> Success

ini\_get -> Success

Operating system: Linux (x86\_64)

PHP version: 5.3.3

done (1863)

Based on your command line parameters, you may be prompted to enter the missing settings. The default value will be given in **bold** . Simply pressing enter key will choose the default value.

Checking database connectivity.done (3107)

Checking database availability.done (3121)

Review settings:

Install web panel files in : /var/www/html/ezlogin/

Install web panel system files in : /var/www/ezlogin/

URI path to access web panel : /ezlogin/

MySQL server : localhost

MySQL port/socket : /var/lib/mysql/mysql.sock

Force HTTPS for web panel? : no

Secure MySQL connection? : no

Accept the above settings? ( y /n/x ) : y

Creating and setting up database... done

Adding ezsh to shells... done

Creating group and users... done

Restoring logs... done

Creating directories... done

Copying files... |

ERROR copying: setup/crontab -> ezadmin

done

Setting access...

done

Setting file modes

done

Setting file owners...

done

Setting file groups...

ERROR chgrp: ezadmin -> root

done

Setting up config... done

Setting up cron... done

Downloading GeoLiteCity database from [www.maxmind.com](http://www.maxmind.com)...

/root/ezlogin\_backup\_v7.8.0\_b381\_Sat\_Jun\_20\_2024\_09\_10\_32\_UTC/setup/setup.php on line

done

#####

Ezeelogin restored. (Log: /var/log/ezlogin\_restore.log )

#####

Please check the log file.

For assistance, please contact support with the content of the log file.

#####

Web panel installed at:

' /var/www/html/ezlogin/ '

( <http://yourdomain.com/ezlogin/> ).

#####

Note: Please check the log file to see if any error occurred.

TODO NOTES:

Enable web server, MySQL server and cron to startup at boot time.

For free assistance, please contact [support@ezeelogin.com](mailto:support@ezeelogin.com)

Thank you for choosing Ezeelogin.

[www.ezeelogin.com](http://www.ezeelogin.com)

- Following shows the help menu for restoring Ezeelogin

```
root@Gateway:~#  
/var/ezlogin_backup_v7.37.11_b381_p8.2.20_Sat_Jun_29_2024_09_02_32_UT  
C.bin -- -help  
  
Creating directory  
ezlogin_backup_v7.37.11_b381_p8.2.20_Sat_Jun_29_2024_09_02_32_UTC  
Verifying archive integrity... 100% MD5 checksums are OK. All good.  
Uncompressing Ezeelogin 7.37.11 backup (PHP 8.2.20,  
Sat_Jun_29_2024_09_02_32_UTC) 100%
```

```

- -
____ _ _ _ _ | | _ _ _ _ ( _ ) _ _ _
/ _ _ / _ / _ _ | / _ _ / _ _ | | ' _
| _ _ // / _ _ / _ _ | ( _ ) | ( _ | | | | |
____/_____|____|____/ _ _ , | _ | _ | _ |
|____/

```

```

#####
# Ezeelogin Restore #
#####

```

Options:

```

-help : Show this help
-version : Show the version
-www <path> : Path from where web server will serve the web panel
files
-sys <path> : Path where web panel will search for its system files
-uri <path> : Request URI path to access the web panel
-dbhost <host> : Specify hostname or IP address of MySQL server
-dbport <port> : Specify the port MySQL server is listening on
-dbsuser <username> : Specify database super (root) user name
-dbspass <password> : Specify database super (root) user password
-force_https <yes/no> : Whether to force HTTPS for web panel
-noauto : Prompt for options
-usebin <absolute_path> : Use the provided binary package instead of
downloading
-lic_timeout <seconds> : Timeout for connecting to Ezeelogin license
server. Default: 30
-proxy_host <host> : Proxy host for connecting to Ezeelogin license
server
-proxy_port <port> : Proxy port for connecting to Ezeelogin license
server
-proxy_user <username> : Proxy user for connecting to Ezeelogin
license server
-proxy_pass <password> : Proxy pass for connecting to Ezeelogin
license server
-mysql_encrypt <yes/no> : Whether to enable secure mysql connection
-mysql_ssl_key <absolute_path> : Path to the private key file for
secure MySQL connection
-mysql_ssl_cert <absolute_path> : Path to the public key certificate
file for secure MySQL connection
-mysql_ssl_ca <absolute_path> : Path to the certificate authority
file for secure MySQL connection
-mysql_ssl_capath <absolute_path> : Path to a directory containing
trusted CA certificates for secure MySQL connection

```

```
-mysql_ssl_cipher <ciphers> : List of *allowed* ciphers to be used  
for the encryption, separated by colons (':')  
-mysql_ssl_verify <yes/no> : Whether to verify the server certificate  
for secure MySQL connection
```

**If you want to restore the Ezeelogin database on a different database host, you need to specify the DB host, port, and other relevant details during the restoration process.**

- Here is an example of **restoring Ezeelogin on a remote database**. Replace dbhost, dbport, and dbuser with the correct values

```
sh ezlogin_backup_v7.37.10_b381_p8.2.20_Sat_Jun_20_2024_09_02_32.UTC.  
bin -- -dbhost 192.168.1.8 -dbport 3306 -dbuser root -dbpasswd
```

- Follow the step below if you **want to do the restore in one step** with your existing settings and **without being prompted**.

```
sh ezlogin_backup_v7.37.10_b381_p8.2.20_Sat_Jun_20_2024_09_02_32.UTC.  
bin -- -skipgeolite -auto -force -ACCEPT_SETTINGS -I_ACCEPT_EULA
```

Replace the backup filename with your own backup file.

You need to check the `/var/log/ezlogin_backup.log` and `/var/log/ezlogin_restore.log` to see if any errors occurred during the backup and restore process

## Related Articles

[How to change the default backup directory of Ezeelogin installation ?](#)

[Migrate jump server installation from one server to another](#)

[How to move servers/migrate servers from one Ezeelogin installation to another?](#)



## Migrate Ezeelogin database to RDS / remote SQL instance

Online URL:

<https://www.ezeelogin.com/kb/article/how-to-create-a-complete-backup-of-ezeelogin-installation-70.html>